

AUSFLEX

PVC Grey Duct

AusFlex PVC Grey Duct is a PVC duct with Rigid helix reinforcement for crush resistance.

This flexible smooth bore duct can be used for both light weight vacuum and transfer applications.

Colour: Grey Temperature Range: -10°C to 60°C Material: PVC	NOM I.D (inch)	NOM I.D (mm)	NOM O.D (mm)	Thickness (mm)	Vacuum (kPa _g)	Bend Radius (mm)	Weight (kg/m)
	2	51	57	3.5	-20	100	0.45
Applications: - Air - Dust - Sawdust - Wood Shavings - Fumes	3	76	84	4.2	-16	155	0.69
	4	102	109	4.7	-13	213	0.99
	5	127	135	5.1	-10	230	1.31
	6	150	162	6.1	-8	375	1.67

*Other sizes available upon request

Plascorp Brisbane
(07) 3035 9200
salesqld@plascorp.com.au

Plascorp Melbourne
(03) 9319 6400
sales@plascorp.com.au

Plascorp Perth
(08) 6278 9400
wasales@plascorp.com.au

PLASTICOAT™ Ducting
CODEMASTER™ Composite Hose
REOMASTER™ Steel Reinforcement
MINEMASTER™ Mine Ventilation
PIPEMASTER™ PVC Pipe

TELEPHONE 1300 301313
www.plascorp.com.au

ABN 34 096 078 527

 **PLASCORP™**